



**HESTORE.HU**

elektronikai alkatrész áruház

**EN:** This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).



# HC-F5V-30L-30LED

## Specification

### I. Product Description

- Every LED works as an individual pixel, it can achieve effects of Full Color Water Running, Chasing and Scanning, which thanks to its high brightness.
- This LED strip could only be linked up to 10 meters, more than 10 meters is strictly prohibited.
- The diameter of the power wires should be based on the actual maximum current, power, and its cabling length (no more than 10 meters), and the voltage of transmission line.
- Widely applied to hotel, KTV entertainment place for interior decorative lighting, etc.

### II. Physical parameters

**Working Voltage:** DC5V

**LED resource:** WS2812B LED(5050 SMD RGB LED with built-in WS2811S IC)

**LED Type:** SMD5050 RGB      **LED Quantity:** 30LEDs/Meter

**Working Current:** 0.06A/Cut ; 1.8A/Meter

**Width:** 10mm      **Length:** 5 Meters per Reel

**Max. Power:** 9Watt/meter      **Viewing angle:**  $\geq 140^\circ$

**Circuit board:** Double FPCB      **FPCB Color:** White/Black

**Lumens:** R60/G120/B59LM

**Package:** Anti-static plastic bag

**Weight:** 235g(Silicone Glue)    95g(Bare board)    195g(Silicone Tube)

**IP Grade:** IP20/IP60/IP65/IP68

**Working Temperature:**  $-40^\circ\text{C} \sim 60^\circ\text{C}$

**Storage temperature:**  $-50^\circ\text{C} \sim 80^\circ\text{C}$

**Lifespan:** 50000 Hours

**Terminal connectors:** 3pin Connector

### III. Glowing Effect



## IV. Distribution wiring diagram

