



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



Heat Shrinkable Tubing 3:1 flexible and coloured

TF31

If higher fire protection is a requirement heat shrinkable tubing TF31 is a good choice. It is used for protection insulation and identification wires, cables and light duty harnesses.

Features and Benefits

- Thin walled, very flexible polyolefin tubing
- Few sizes cover a wide range of diameters allowing reduced inventory
- Fast shrinking and low shrink temperature
- Flame-retardant, UL224 VW1 listed




Detailed Information about Heatguns please refer to page 529.




Cut lengths available on request. Please contact us!



One Step to the Web!



RoHS ✓



TF31 with 3:1 shrink ratio allowing for a wider range of application.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	3:1
Operating Temperature	-55 °C to +135 °C
Minimum Shrink Temperature	+90 °C
Longitudinal change after shrinkage	+5 %/-15 %
Dielectric Strength	37 kV/mm
Flammability	ASTM D876
Specifications	CSA, UL224 125 °C 600V VW-1

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TF31-1.5/0.5	1.5	0.5	0.50	30 m	Black (BK)	333-30150
	1.5	0.5	0.50	30 m	Blue (BU)	333-30156
	1.5	0.5	0.50	30 m	Green (GN)	333-30155
	1.5	0.5	0.50	30 m	Green-Yellow (GNYE)	333-30157
	1.5	0.5	0.50	30 m	Red (RD)	333-30152
	1.5	0.5	0.50	30 m	White (WH)	333-30159
	1.5	0.5	0.50	30 m	Yellow (YE)	333-30154
	1.5	0.5	0.50	300 m	Black (BK)	333-20150
TF31-3/1	3.0	1.0	0.60	30 m	Black (BK)	333-30300
	3.0	1.0	0.60	30 m	Blue (BU)	333-30306
	3.0	1.0	0.60	30 m	Green (GN)	333-30305
	3.0	1.0	0.60	30 m	Green-Yellow (GNYE)	333-30307
	3.0	1.0	0.60	30 m	Red (RD)	333-30302
	3.0	1.0	0.60	30 m	White (WH)	333-30309
	3.0	1.0	0.60	30 m	Yellow (YE)	333-30304
	3.0	1.0	0.60	150 m	Black (BK)	333-40300

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



Heat Shrinkable Tubing 3:1 flexible and coloured

TF31




Heat Shrinkable Tubing 3:1

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TF31-6/2	6.0	2.0	0.70	30 m	Black (BK)	333-30600
	6.0	2.0	0.70	30 m	Blue (BU)	333-30606
	6.0	2.0	0.70	30 m	Green (GN)	333-30605
	6.0	2.0	0.70	30 m	Green-Yellow (GNYE)	333-30607
	6.0	2.0	0.70	30 m	Red (RD)	333-30602
	6.0	2.0	0.70	30 m	White (WH)	333-30609
	6.0	2.0	0.70	30 m	Yellow (YE)	333-30604
TF31-9/3	9.0	3.0	0.80	150 m	Black (BK)	333-40600
	9.0	3.0	0.80	30 m	Black (BK)	333-30900
	9.0	3.0	0.80	30 m	Blue (BU)	333-30906
	9.0	3.0	0.80	30 m	Green (GN)	333-30905
	9.0	3.0	0.80	30 m	Green-Yellow (GNYE)	333-30907
	9.0	3.0	0.80	30 m	Red (RD)	333-30902
	9.0	3.0	0.80	30 m	White (WH)	333-30909
TF31-12/4	12.0	4.0	0.85	30 m	Black (BK)	333-20900
	12.0	4.0	0.85	30 m	Blue (BU)	333-31200
	12.0	4.0	0.85	30 m	Green (GN)	333-31206
	12.0	4.0	0.85	30 m	Green (GN)	333-31205
	12.0	4.0	0.85	30 m	Green-Yellow (GNYE)	333-31207
	12.0	4.0	0.85	30 m	Red (RD)	333-31202
	12.0	4.0	0.85	30 m	White (WH)	333-31209
TF31-18/6	18.0	6.0	1.00	30 m	Black (BK)	333-31204
	18.0	6.0	1.00	30 m	Black (BK)	333-31200
	18.0	6.0	1.00	30 m	Blue (BU)	333-21200
	18.0	6.0	1.00	30 m	Blue (BU)	333-31806
	18.0	6.0	1.00	30 m	Green (GN)	333-31805
	18.0	6.0	1.00	30 m	Green (GN)	333-31805
	18.0	6.0	1.00	30 m	Green-Yellow (GNYE)	333-31807
18.0	6.0	1.00	30 m	Red (RD)	333-31802	
18.0	6.0	1.00	30 m	Red (RD)	333-31802	
18.0	6.0	1.00	30 m	White (WH)	333-31809	
18.0	6.0	1.00	30 m	White (WH)	333-31809	
18.0	6.0	1.00	30 m	Yellow (YE)	333-31804	
18.0	6.0	1.00	30 m	Yellow (YE)	333-31804	
18.0	6.0	1.00	60 m	Black (BK)	333-41800	

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



Heat Shrinkable Tubing 3:1 flexible and coloured

TF31



Heat Shrinkable Tubing 3:1



Detailed Information about Heatguns please refer to page 529.

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TF31-24/8	24.0	8.0	1.20	30 m	Black (BK)	333-32400
	24.0	8.0	1.20	30 m	Blue (BU)	333-32406
	24.0	8.0	1.20	30 m	Green (GN)	333-32405
	24.0	8.0	1.20	30 m	Green-Yellow (GNYE)	333-32407
	24.0	8.0	1.20	30 m	Red (RD)	333-32402
	24.0	8.0	1.20	30 m	White (WH)	333-32409
	24.0	8.0	1.20	30 m	Yellow (YE)	333-32404
	24.0	8.0	1.20	60 m	Black (BK)	333-42400
TF31-40/13	40.0	13.0	1.25	30 m	Black (BK)	333-34000
	40.0	13.0	1.25	30 m	Blue (BU)	333-34006
	40.0	13.0	1.25	30 m	Green (GN)	333-34005
	40.0	13.0	1.25	30 m	Green-Yellow (GNYE)	333-34007
	40.0	13.0	1.25	30 m	Red (RD)	333-34002
	40.0	13.0	1.25	30 m	White (WH)	333-34009
	40.0	13.0	1.25	30 m	Yellow (YE)	333-34004
	40.0	13.0	1.25	60 m	Black (BK)	333-24000

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.