



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Polarized flat cables



RoHS
Conformity

Applications:
Polarized flat cable.
Cable for electronics, loudspeakers, Home Theatre and Hi-Fi Car systems.

Characteristics:
Conductors: n. 1 O.F.C. red copper
n. 1 O.F.C. tinned copper
Special PVC
Insulation:
Sheath colours: **Grey**
Black or White *on demand*

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Elementary wire conductor Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C100	2	2 x 0,35	22	0,20	1,9 x 3,9	100	B	1,1
		2 x 0,50	20	0,20	2,0 x 4,1	100	B	1,5
		2 x 0,75	18	0,20	2,2 x 4,5	100	B	2,1
		2 x 1,00	17	0,20	2,8 x 5,7	100	B	2,9
		2 x 2,00	14	0,20	3,7 x 7,1	100	B	5,5



Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
60	49	-15 / +70
45	49	-15 / +70
32	49	-15 / +70
21	49	-15 / +70
14	49	-15 / +70

RoHS
Conformity

Red and Black flat cables



Applications:
Red and black flat cable.
Cable for loudspeakers, Home Theatre and Hi-Fi Car systems.

Characteristics:
Conductors: O.F.C. red copper
Insulation: Special PVC
Sheath colour: Red-black

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Elementary wire conductor Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C101	2	2 x 0,35	22	0,20	1,9 x 3,9	100	B	1,1
		2 x 0,50	20	0,20	2,0 x 4,1	100	B	1,5
		2 x 0,75	18	0,20	2,2 x 4,5	100	B	2,1
		2 x 1,00	17	0,20	2,5 x 5,1	100	B	2,9
		2 x 1,50	16	0,25	3,1 x 6,2	100	B	4,0
C102	2	2 x 2,00	14	0,25	3,5 x 7,1	100	B	5,5
		2 x 2,50	13	0,25	3,7 x 7,4	100	B	6,4



Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
60	49	-15 / +70
45	49	-15 / +70
32	49	-15 / +70
21	49	-15 / +70
16	49	-15 / +70
14	49	-15 / +70
12	49	-15 / +70

RoHS
Conformity

Multicolour flat cable



Applications:
Multicolour flat cable.
Cable for electronics, loudspeakers, Home Theatre and Hi-Fi Car systems.

Characteristics:
Conductors: O.F.C. red copper
Cond. Insulation: PVC
Core colours: Blue, White, Black, Red
Sheath: Special PVC
Sheath colour: Transparent

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Elementary wire conductor Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C104	4	4 x 1,00	17	0,20	3,0 x 12,0	100	B	6,0



Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
21	49	-15 / +70