



**HESTORE.HU**

elektronikai alkatrész áruház

**EN:** This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).

## 3-TERMINAL POSITIVE VOLTAGE REGULATOR


### ■ GENERAL DESCRIPTION

The NJM7800 series of monolithic 3-Terminal Positive Voltage Regulators is constructed using the New JRC Planar epitaxial process. These regulators employ internal current-limiting, thermal-shutdown and safe-area compensation making them essentially indestructible. If adequate heat sinking is provided, they can deliver over 1A output current. They are intended as fixed voltage regulators in a wide range of applications including local (on card) regulation for elimination of distribution problems associated with single point regulation. In addition to use as fixed voltage regulators, these devices can be used with external components to obtain adjustable output voltages and currents.

### ■ FEATURES


- Internal Short Circuit Current Limit
- Internal Thermal Overload Protection
- Excellent Ripple Rejection
- Guaranteed 1.5A Output Current
- Package Outline            TO-220F, TO-252
- Bipolar Technology

### ■ EQUIVALENT CIRCUIT




### ■ PACKAGE OUTLINE

( TO-220F )



( TO-252 )



#### NJM7800FA

- 1. IN
- 2. GND
- 3. OUT

#### NJM7800DL1A

- 1. IN
- 2. GND
- 3. OUT

(note) The radiation fin is connected pin 2.

# NJM7800

## ■ ABSOLUTE MAXIMUM RATINGS

(Ta = 25°C)

PARAMETER	SYMBOL	MAXIMUM RATINGS		UNIT
Input Voltage	V <sub>IN</sub>	7805 to 7810 7812 to 7815 7818 to 7824	35 35 40	V
Storage Temperature Range	T <sub>stg</sub>	-40 to +150		°C
Operating Temperature Range	Operating Junction Temperature		T <sub>j</sub>	-40 to +150
	Operating Temperature		T <sub>opr</sub>	-40 to +85
Power Dissipation	P <sub>D</sub>	TO-220F TO-252	16(T <sub>C</sub> ≤70°C) 10(T <sub>C</sub> =25°C) 1(T <sub>a</sub> ≤25°C)	W

## ■ ELECTRICAL CHARACTERISTICS (C<sub>I</sub> = 0.33μF, C<sub>O</sub> = 0.1μF, T<sub>j</sub> = 25°C)

Measurement is to be conducted in pulse testing.

PARAMETER	SYMBOL	TEST CONDITIONS	TO-220F			TO-252			UNIT
			MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
<b>NJM7805FA/DL1A</b>									
Output Voltage	V <sub>O</sub>	V <sub>IN</sub> =10V, I <sub>O</sub> =0.5A	4.8	5.0	5.2	4.8	5.0	5.2	V
Line Regulation	ΔV <sub>O</sub> - V <sub>IN</sub>	V <sub>IN</sub> =7 to 25V, I <sub>O</sub> =0.5A	-	3	50	-	3	100	mV
Load Regulation	ΔV <sub>O</sub> - I <sub>O</sub>	V <sub>IN</sub> =10V, I <sub>O</sub> =0.005 to 1.5A	-	15	50	-	15	100	mV
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =10V, I <sub>O</sub> =0mA	-	4.2	6.0	-	4.2	6.0	mA
Average Temperature Coefficient of Output Voltage	ΔV <sub>O</sub> /ΔT	V <sub>IN</sub> =10V, I <sub>O</sub> =5mA	-	-0.5	-	-	-0.5	-	mV/°C
Ripple Rejection	RR	V <sub>IN</sub> =10V, I <sub>O</sub> =0.5A, e <sub>in</sub> =2V <sub>P-P</sub> , f=120Hz	68	78	-	68	78	-	dB
Output Noise Voltage	V <sub>NO</sub>	V <sub>IN</sub> =10V, BW=10Hz to 100kHz, I <sub>O</sub> =0.5A	-	45	-	-	45	-	μV
<b>NJM7806FA/DL1A</b>									
Output Voltage	V <sub>O</sub>	V <sub>IN</sub> =11V, I <sub>O</sub> =0.5A	5.75	6.0	6.25	5.75	6.0	6.25	V
Line Regulation	ΔV <sub>O</sub> - V <sub>IN</sub>	V <sub>IN</sub> =8 to 25V, I <sub>O</sub> =0.5A	-	5	60	-	5	120	mV
Load Regulation	ΔV <sub>O</sub> - I <sub>O</sub>	V <sub>IN</sub> =11V, I <sub>O</sub> =0.005 to 1.5A	-	15	60	-	15	120	mV
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =11V, I <sub>O</sub> =0mA	-	4.3	6.0	-	4.3	6.0	mA
Average Temperature Coefficient of Output Voltage	ΔV <sub>O</sub> /ΔT	V <sub>IN</sub> =11V, I <sub>O</sub> =5mA	-	-0.6	-	-	-0.6	-	mV/°C
Ripple Rejection	RR	V <sub>IN</sub> =11V, I <sub>O</sub> =0.5A, e <sub>in</sub> =2V <sub>P-P</sub> , f=120Hz	65	75	-	65	75	-	dB
Output Noise Voltage	V <sub>NO</sub>	V <sub>IN</sub> =11V, BW=10Hz to 100kHz, I <sub>O</sub> =0.5A	-	45	-	-	45	-	μV

■ **ELECTRICAL CHARACTERISTICS** ( $C_1 = 0.33\mu\text{F}$ ,  $C_O = 0.1\mu\text{F}$ ,  $T_j = 25^\circ\text{C}$ )

Measurement is to be conducted in pulse testing.

PARAMETER	SYMBOL	TEST CONDITIONS	TO-220F			TO-252			UNIT
			MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
<b>NJM7808FA/DL1A</b>									
Output Voltage	$V_O$	$V_{IN}=14\text{V}$ , $I_O=0.5\text{A}$	7.7	8.0	8.3	7.7	8.0	8.3	V
Line Regulation	$\Delta V_O - V_{IN}$	$V_{IN}=10.5$ to $25\text{V}$ , $I_O=0.5\text{A}$	-	6	80	-	6	160	mV
Load Regulation	$\Delta V_O - I_O$	$V_{IN}=14\text{V}$ , $I_O=0.005$ to $1.5\text{A}$	-	15	80	-	15	160	mV
Quiescent Current	$I_Q$	$V_{IN}=14\text{V}$ , $I_O=0\text{mA}$	-	4.3	6.0	-	4.3	6.0	mA
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=14\text{V}$ , $I_O=5\text{mA}$	-	-0.8	-	-	-0.8	-	mV/°C
Ripple Rejection	RR	$V_{IN}=14\text{V}$ , $I_O=0.5\text{A}$ , $e_{in}=2V_{P-P}$ , $f=120\text{Hz}$	62	72	-	62	72	-	dB
Output Noise Voltage	$V_{NO}$	$V_{IN}=14\text{V}$ , $BW=10\text{Hz}$ to $100\text{kHz}$ , $I_O=0.5\text{A}$	-	55	-	-	55	-	$\mu\text{V}$
<b>NJM7809FA/DL1A</b>									
Output Voltage	$V_O$	$V_{IN}=15\text{V}$ , $I_O=0.5\text{A}$	8.65	9.0	9.35	8.65	9.0	9.35	V
Line Regulation	$\Delta V_O - V_{IN}$	$V_{IN}=11.5$ to $25\text{V}$ , $I_O=0.5\text{A}$	-	7	90	-	7	180	mV
Load Regulation	$\Delta V_O - I_O$	$V_{IN}=15\text{V}$ , $I_O=0.005$ to $1.5\text{A}$	-	15	90	-	15	180	mV
Quiescent Current	$I_Q$	$V_{IN}=15\text{V}$ , $I_O=0\text{mA}$	-	4.3	6.0	-	4.3	6.0	mA
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=15\text{V}$ , $I_O=5\text{mA}$	-	-0.9	-	-	-0.9	-	mV/°C
Ripple Rejection	RR	$V_{IN}=15\text{V}$ , $I_O=0.5\text{A}$ , $e_{in}=2V_{P-P}$ , $f=120\text{Hz}$	62	72	-	62	72	-	dB
Output Noise Voltage	$V_{NO}$	$V_{IN}=15\text{V}$ , $BW=10\text{Hz}$ to $100\text{kHz}$ , $I_O=0.5\text{A}$	-	60	-	-	60	-	$\mu\text{V}$
<b>NJM7810FA/DL1A</b>									
Output Voltage	$V_O$	$V_{IN}=17\text{V}$ , $I_O=0.5\text{A}$	9.60	10.0	10.4	9.60	10.0	10.4	V
Line Regulation	$\Delta V_O - V_{IN}$	$V_{IN}=12.5$ to $25\text{V}$ , $I_O=0.5\text{A}$	-	7	100	-	7	200	mV
Load Regulation	$\Delta V_O - I_O$	$V_{IN}=17\text{V}$ , $I_O=0.005$ to $1.5\text{A}$	-	15	130	-	15	200	mV
Quiescent Current	$I_Q$	$V_{IN}=17\text{V}$ , $I_O=0\text{mA}$	-	4.3	6.0	-	4.3	6.0	mA
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=17\text{V}$ , $I_O=5\text{mA}$	-	-0.9	-	-	-1.0	-	mV/°C
Ripple Rejection	RR	$V_{IN}=17\text{V}$ , $I_O=0.5\text{A}$ , $e_{in}=2V_{P-P}$ , $f=120\text{Hz}$	62	72	-	62	72	-	dB
Output Noise Voltage	$V_{NO}$	$V_{IN}=17\text{V}$ , $BW=10\text{Hz}$ to $100\text{kHz}$ , $I_O=0.5\text{A}$	-	60	-	-	65	-	$\mu\text{V}$

# NJM7800

## ■ ELECTRICAL CHARACTERISTICS ( $C_I = 0.33\mu\text{F}$ , $C_O = 0.1\mu\text{F}$ , $T_j = 25^\circ\text{C}$ )

Measurement is to be conducted in pulse testing.

PARAMETER	SYMBOL	TEST CONDITIONS	TO-220F			TO-252			UNIT
			MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
<b>NJM7812FA/DL1A</b>									
Output Voltage	$V_O$	$V_{IN}=19\text{V}$ , $I_O=0.5\text{A}$	11.5	12.0	12.5	11.5	12.0	12.5	V
Line Regulation	$\Delta V_O - V_{IN}$	$V_{IN}=14.5$ to $30\text{V}$ , $I_O=0.5\text{A}$	-	10	120	-	10	240	mV
Load Regulation	$\Delta V_O - I_O$	$V_{IN}=19\text{V}$ , $I_O=0.005$ to $1.5\text{A}$	-	25	120	-	25	240	mV
Quiescent Current	$I_Q$	$V_{IN}=19\text{V}$ , $I_O=0\text{mA}$	-	4.3	6.0	-	4.3	6.0	mA
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=19\text{V}$ , $I_O=5\text{mA}$	-	-1.2	-	-	-1.2	-	$\text{mV}/^\circ\text{C}$
Ripple Rejection	RR	$V_{IN}=19\text{V}$ , $I_O=0.5\text{A}$ , $e_{in}=2\text{V}_{P-P}$ , $f=120\text{Hz}$	61	71	-	61	71	-	dB
Output Noise Voltage	$V_{NO}$	$V_{IN}=19\text{V}$ , $\text{BW}=10\text{Hz}$ to $100\text{kHz}$ , $I_O=0.5\text{A}$	-	75	-	-	75	-	$\mu\text{V}$
<b>NJM7815FA/DL1A</b>									
Output Voltage	$V_O$	$V_{IN}=23\text{V}$ , $I_O=0.5\text{A}$	14.4	15.0	15.6	14.4	15.0	15.6	V
Line Regulation	$\Delta V_O - V_{IN}$	$V_{IN}=17.5$ to $30\text{V}$ , $I_O=0.5\text{A}$	-	11	150	-	11	300	mV
Load Regulation	$\Delta V_O - I_O$	$V_{IN}=23\text{V}$ , $I_O=0.005$ to $1.5\text{A}$	-	35	150	-	35	300	mV
Quiescent Current	$I_Q$	$V_{IN}=23\text{V}$ , $I_O=0\text{mA}$	-	4.4	6.0	-	4.4	6.0	mA
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=23\text{V}$ , $I_O=5\text{mA}$	-	-1.5	-	-	-1.5	-	$\text{mV}/^\circ\text{C}$
Ripple Rejection	RR	$V_{IN}=23\text{V}$ , $I_O=0.5\text{A}$ , $e_{in}=2\text{V}_{P-P}$ , $f=120\text{Hz}$	60	70	-	60	70	-	dB
Output Noise Voltage	$V_{NO}$	$V_{IN}=23\text{V}$ , $\text{BW}=10\text{Hz}$ to $100\text{kHz}$ , $I_O=0.5\text{A}$	-	90	-	-	90	-	$\mu\text{V}$
<b>NJM7818FA/DL1A</b>									
Output Voltage	$V_O$	$V_{IN}=27\text{V}$ , $I_O=0.5\text{A}$	17.3	18.0	18.7	17.3	18.0	18.7	V
Line Regulation	$\Delta V_O - V_{IN}$	$V_{IN}=21$ to $33\text{V}$ , $I_O=0.5\text{A}$	-	15	180	-	15	360	mV
Load Regulation	$\Delta V_O - I_O$	$V_{IN}=27\text{V}$ , $I_O=0.005$ to $1.5\text{A}$	-	55	180	-	55	360	mV
Quiescent Current	$I_Q$	$V_{IN}=27\text{V}$ , $I_O=0\text{mA}$	-	4.5	6.0	-	4.5	6.0	mA
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=27\text{V}$ , $I_O=5\text{mA}$	-	-1.8	-	-	-1.8	-	$\text{mV}/^\circ\text{C}$
Ripple Rejection	RR	$V_{IN}=27\text{V}$ , $I_O=0.5\text{A}$ , $e_{in}=2\text{V}_{P-P}$ , $f=120\text{Hz}$	59	69	-	59	69	-	dB
Output Noise Voltage	$V_{NO}$	$V_{IN}=27\text{V}$ , $\text{BW}=10\text{Hz}$ to $100\text{kHz}$ , $I_O=0.5\text{A}$	-	100	-	-	100	-	$\mu\text{V}$
<b>NJM7820FA/DL1A</b>									
Output Voltage	$V_O$	$V_{IN}=29\text{V}$ , $I_O=0.5\text{A}$	19.2	20.0	20.8	19.2	20.0	20.8	V
Line Regulation	$\Delta V_O - V_{IN}$	$V_{IN}=23$ to $35\text{V}$ , $I_O=0.5\text{A}$	-	16	200	-	16	400	mV
Load Regulation	$\Delta V_O - I_O$	$V_{IN}=29\text{V}$ , $I_O=0.005$ to $1.5\text{A}$	-	61	200	-	61	400	mV
Quiescent Current	$I_Q$	$V_{IN}=29\text{V}$ , $I_O=0\text{mA}$	-	4.5	6.0	-	4.5	6.0	mA
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=29\text{V}$ , $I_O=5\text{mA}$	-	-2.0	-	-	-2.0	-	$\text{mV}/^\circ\text{C}$
Ripple Rejection	RR	$V_{IN}=29\text{V}$ , $I_O=0.5\text{A}$ , $e_{in}=2\text{V}_{P-P}$ , $f=120\text{Hz}$	58	68	-	58	68	-	dB
Output Noise Voltage	$V_{NO}$	$V_{IN}=29\text{V}$ , $\text{BW}=10\text{Hz}$ to $100\text{kHz}$ , $I_O=0.5\text{A}$	-	120	-	-	120	-	$\mu\text{V}$



■ **ELECTRICAL CHARACTERISTICS** ( $C_1 = 0.33\mu\text{F}$ ,  $C_O = 0.1\mu\text{F}$ ,  $T_j = 25^\circ\text{C}$ )

Measurement is to be conducted in pulse testing.

PARAMETER	SYMBOL	TEST CONDITIONS	TO-220F			TO-252			UNIT
			MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
<b>NJM7824FA/DL1A</b>									
Output Voltage	$V_O$	$V_{IN}=33\text{V}$ , $I_O=0.5\text{A}$	23.0	24.0	25.0	23.0	24.0	25.0	V
Line Regulation	$\Delta V_O - V_{IN}$	$V_{IN}=27$ to $38\text{V}$ , $I_O=0.5\text{A}$	-	18	240	-	18	480	mV
Load Regulation	$\Delta V_O - I_O$	$V_{IN}=33\text{V}$ , $I_O=0.005$ to $1.5\text{A}$	-	65	240	-	65	480	mV
Quiescent Current	$I_Q$	$V_{IN}=33\text{V}$ , $I_O=0\text{mA}$	-	4.6	6.0	-	4.6	6.0	mA
Average Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T$	$V_{IN}=33\text{V}$ , $I_O=5\text{mA}$	-	-2.4	-	-	-2.4	-	mV/°C
Ripple Rejection	RR	$V_{IN}=33\text{V}$ , $I_O=0.5\text{A}$ , $e_{in}=2\text{V}_{P-P}$ , $f=120\text{Hz}$	56	66	-	56	66	-	dB
Output Noise Voltage	$V_{No}$	$V_{IN}=33\text{V}$ , $BW=10\text{Hz}$ to $100\text{kHz}$ , $I_O=0.5\text{A}$	-	120	-	-	120	-	$\mu\text{V}$

# NJM7800



## POWER DISSIPATION VS. AMBIENT TEMPERATURE



## TEST CIRCUIT

1. Output Voltage, Line Regulation, Load Regulation, Quiescent Current, Average Temperature Coefficient of Output Voltage, Output Noise Voltage

2. Ripple Rejection



## ■ Input Capacitor $C_{IN}$

Input Capacitor  $C_{IN}$  is required to prevent oscillation and reduce power supply ripple for applications when high power supply impedance or a long power supply line.

Therefore, use the recommended  $C_{IN}$  value (refer to conditions of ELECTRIC CHARACTERISTIC) or larger and should connect between GND and  $V_{IN}$  as shortest path as possible to avoid the problem.

## ■ Output Capacitor $C_O$

Output capacitor ( $C_O$ ) will be required for a phase compensation of the internal error amplifier.

The capacitance and the equivalent series resistance (ESR) influence to stable operation of the regulator.

Use of a smaller  $C_O$  may cause excess output noise or oscillation of the regulator due to lack of the phase compensation.

On the other hand, Use of a larger  $C_O$  reduces output noise and ripple output, and also improves output transient response when rapid load change.

Therefore, use the recommended  $C_O$  value (refer to conditions of ELECTRIC CHARACTERISTIC) or larger and should connect between GND and  $V_{OUT}$  as shortest path as possible for stable operation

In addition, you should consider varied characteristics of capacitor (a frequency characteristic, a temperature characteristic, a DC bias characteristic and so on) and unevenness peculiar to a capacitor supplier enough.


When selecting  $C_O$ , recommend that have withstand voltage margin against output voltage and superior temperature characteristic though




# NJM7800

## ■ TYPICAL CHARACTERISTICS


**NJM7805 Output Voltage vs. Temperature**



**NJM7808 Output Voltage vs. Temperature**




**NJM78M00 Series Equivalent Series Resistance vs. Output Current**




## ■ TYPICAL CHARACTERISTICS


### NJM7805/15/24 Output Characteristics ( $I_o=0.5A, T_j=25^\circ C$ )




### NJM7805 Dropout Characteristics ( $T_j=25^\circ C$ )



### NJM7812 Dropout Characteristics ( $T_j=25^\circ C$ )



### NJM7805/15/24 Load Characteristics ( $T_j=25^\circ C$ )




# NJM7800

## ■ TYPICAL CHARACTERISTICS


### NJM7800 Series Short Circuit Output Current

( $T_j=25^\circ\text{C}$ ,  $\infty$  Heat Sink)




### NJM7805/24 Quiescent Current vs. Input Voltage


( $T_j=25^\circ\text{C}$ .)



### NJM7805/15/24 Output Voltage vs. Junction Temperature



### NJM7805/15/24 Ripple Rejection vs. Frequency



$V_{IN} = 10\text{V (05)}$   $e_{in} = 2V_{P-P}$   
 19V (12)  
 33V (24)  
 $T_j = 25^\circ\text{C}$

**[CAUTION]**  
 The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Nisshinbo Micro Devices:

[NJM7818FA](#) [NJM7808FA](#) [NJM7812DL1A-TE1](#) [NJM7805FA](#) [NJM7809FA](#) [NJM7808DL1A-TE2](#) [NJM7808DL1A-TE1](#)  
[NJM7809DL1A-TE1](#) [NJM7815FA](#) [NJM7815DL1A-TE1](#) [NJM7820DL1A-TE1](#) [NJM7824DL1A-TE1](#) [NJM7824FA](#)  
[NJM7805DL1A-TE1](#) [NJM7805DL1A-TE2](#) [NJM7820FA](#) [NJM7812FA](#) [NJM7810DL1A-TE1](#) [NJM7806FA](#) [NJM7810FA](#)  
[NJM7818DL1A-TE1](#) [NJM7806DL1A-TE1](#) [NJM7809DL1A-TE2](#) [NJM7818DL1A-TE2](#) [NJM7815DL1A-TE2](#)  
[NJM7824DL1A-TE2](#) [NJM7812DL1A-TE2](#) [NJM7824FA-TE1](#) [NJM7812FA-TE1](#) [NJM7808FA-TE1](#) [NJM7809FA-TE1](#)  
[NJM7818FA-TE1](#) [NJM7806FA-TE1](#) [NJM7815FA-TE1](#) [NJM7820FA-TE1](#) [NJM7810DL1A-TE2](#) [NJM7805FA-TE1](#)  
[NJM7810FA-TE1](#)