




HESTORE.HU

elektronikai alkatrész áruház


EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.


Zeichnung
Drawing



Art. Nr./ No.	Länge/length	Farbe/color
67975	0,5 m	schwarz/ black
67193	0,5 m	weiß/white
67976	1,0 m	schwarz/ black
67194	1,0 m	weiß/white
66507	1,5 m	schwarz/ black
66508	2 m	schwarz/ black
66509	3 m	schwarz/ black



Schaltplan
Wiring diagram



USB 3.1 SuperSpeed+ Kabel USB C
Anschlüsse: 2x USB-C-Stecker
Materialien:
Isolierung: PVC; schwarz
Kontakte: vergoldet
Stecker: vernickelt
Innenleiter: verzinnnes Kupfer
Kabelaufbau: [34AWG*1C+SP+AL/MY]+8COAX+

Datenrate: max. 5 Gbit/s; Generation 1
USB-Standard: 3.1
Nennstromstärke: 3 A
Konformität: RoHS

USB 3.1 SuperSpeed+ cable USB C
Connectors: 2x USB-C plug
Materials:

Insulation: PVC; black
Contacts: gold-plated
Plugs: vernickelt
Inner conductor: TC
Cable constructin: [34AWG*1C+SP+AL/MY]+8COAX+
34AWG*1P+
34AWG*3C+
28AWG*2C+AL/MY+
B (85 %TC)
Data rate: max. 5 Gbit/s; Generation 1
USB standard: 3.1
Nominal current: 3 A
Conformity: RoHS

Änderungen

Datum	Name	gez.:	Datum	Name	Bezeichnung	Blatt
02.03.2018	tf	gez.:	14.08.2015	tf	USB 3.1 C/C	goobay®
31.07.2019	ss	gepr.:	14.08.2015	tf		
26.03.2020	nw	Norm:	Änderungen vorbehalten / Subject to change		Zeichnungs-Nr.:	von