







HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 125V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: PBT,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A1250H-02P	1.25	4.25
A1250H-03P	2.50	5.50
A1250H-04P	3.75	6.75
A1250H-05P	5.00	8.00
A1250H-06P	6.25	9.25
A1250H-07P	7.50	10.50
A1250H-08P	8.75	11.75
A1250H-09P	10.00	13.00
A1250H-10P	11.25	14.25
A1250H-11P	12.50	15.50
A1250H-12P	13.75	16.75
A1250H-13P	15.00	18.00
A1250H-14P	16.25	19.25
A1250H-15P	17.50	20.50
A1250H-16P	18.75	21.75
A1250H-17P	20.00	23.00
A1250H-18P	21.25	24.25

			UNIT	SCALE	SHEET	TITLE:
			mm		1 of 1	
			DRAWN BY	APPROVED BY		1.25mm PITCH HOUSING
			董正一	董正一		
			2001.02.01	2001.02.01		
			GENERAL TOLERANCE			
B0	NEW RELEASE	2006.06.23	X.X ± 0.25	ANGLE ±		DRAW NO. : A1250H-XP
REV.	DESCRIPTION	DATE	X.XX ± 0.15			
			X.XXX ± 0.05			